FLOWTITE PRODUCTS

RAINWATER HARVESTING

NOTE: CUSTOMER SUPPLIED FLEXIBLE PIPING COUPLING REQUIRED ON TANGENTIALLY MTD. NOZZLES, STUB-OUTS & NPT FITTINGS.

SHELL CODES: 1-E6S06SD, 1-E6SECSD FRP ACCESS COLLAR w/ADHESIVE CHANNEL INLET/FILL FTG.-THIS IS AN IAPMO APPROVED TANK COMPLIANCE STANDARDS AND CODES: IAPMO/ANSI Z1002 UNIFORM PLUMBING CODE (UPC) $\boxtimes \oplus$ MFG. PER PE-C22.85 TANK VENT FTG. PVC ACCESS RISER w/WATERTIGHT LOCKING COVER STUB-OUT (OVERFLOW) 6'-0" I.D. 6'-2 3/4" O.D. 16-1/2" TYP. 2'-0 1/8" -6'-10 1/2"-2'-2 7/8" -11'-1 1/2"-OPTIONAL 18"x 8"x 14' DEADMAN

THIS DIAGRAM IS THE PROPERTY OF CONTAINMENT SOLUTIONS, INC., AND IS FOR ILLUSTRATION PURPOSES ONLY. IT IS NOT TO BE RELIED UPON FOR ANY OTHER PURPOSE. NO WARRANTY OF MERCHANT ABILITY OF FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER KIND, EXPRESSED OR IMPLIED IS HEREBY MADE. COPYRIGHT @ 2016 CONTAINMENT SOLUTIONS, INC. ALL RIGHTS RESERVED.

IAPMO Z1002 MINIMUM REQUIRED TANK OPENINGS

1-ACCESS COLLAR OPENING (24", 30" or 36")

1-ACCESS RISER w/WATERTIGHT LOCKING COVER

1-INLET/FILL FITTING (4" MIN)

1-TANK OVERFLOW (EQUAL TO THE INLET)

1-TANK VENT (EQUAL TO LARGER-INLET OR OVERFLOW)

SWT D-6 (6')-2000			DATE: 7/28/2016
IAPMO RAINWATER HARVESTING			DRAWN BY: R.OXNER
CONT	AINMENT	CAPACITY: 2,147	REVISED: 4/16/17-A
	J T I O N S _®	WEIGHT: DRY/WET 1050	DWG NUMBER: 6-02 IRWH