

(6') DWT-6 TYPE II 2,500 GALLON

DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS
1/8	2	6 1/8	112	12 1/8	298	18 1/8	530	24 1/8	793	30 1/8	1075
1/4	3	6 1/4	115	12 1/4	302	18 1/4	535	24 1/4	799	30 1/4	1081
3/8	4	6 3/8	119	12 3/8	307	18 3/8	541	24 3/8	804	30 3/8	1087
1/2	5	6 1/2	122	12 1/2	311	18 1/2	546	24 1/2	810	30 1/2	1093
5/8	6	6 5/8	125	12 5/8	316	18 5/8	551	24 5/8	816	30 5/8	1099
3/4	7	6 3/4	129	12 3/4	320	18 3/4	556	24 3/4	822	30 3/4	1105
7/8	9	6 7/8	132	12 7/8	325	18 7/8	562	24 7/8	827	30 7/8	1111
1	10	7	135	13	329	19	567	25	833	31	1117
1 1/8	12	7 1/8	139	13 1/8	334	19 1/8	572	25 1/8	839	31 1/8	1123
1 1/4	13	7 1/4	142	13 1/4	339	19 1/4	577	25 1/4	845	31 1/4	1129
1 3/8	15	7 3/8	146	13 3/8	343	19 3/8	583	25 3/8	850	31 3/8	1135
1 1/2	17	7 1/2	149	13 1/2	348	19 1/2	588	25 1/2	856	31 1/2	1141
1 5/8	18	7 5/8	153	13 5/8	352	19 5/8	593	25 5/8	862	31 5/8	1147
1 3/4	20	7 3/4	157	13 3/4	357	19 3/4	599	25 3/4	868	31 3/4	1153
1 7/8	22	7 7/8	160	13 7/8	362	19 7/8	604	25 7/8	874	31 7/8	1159
2	24	8	164	14	366	20	609	26	879	32	1165
2 1/8	26	8 1/8	168	14 1/8	371	20 1/8	615	26 1/8	885	32 1/8	1171
2 1/4	28	8 1/4	171	14 1/4	376	20 1/4	620	26 1/4	891	32 1/4	1177
2 3/8	30	8 3/8	175	14 3/8	381	20 3/8	626	26 3/8	897	32 3/8	1183
2 1/2	32	8 1/2	179	14 1/2	385	20 1/2	631	26 1/2	903	32 1/2	1190
2 5/8	35	8 5/8	183	14 5/8	390	20 5/8	637	26 5/8	909	32 5/8	1196
2 3/4	37	8 3/4	186	14 3/4	395	20 3/4	642	26 3/4	915	32 3/4	1202
2 7/8	39	8 7/8	190	14 7/8	400	20 7/8	647	26 7/8	920	32 7/8	1208
3	41	9	194	15	405	21	653	27	926	33	1214
3 1/8	44	9 1/8	198	15 1/8	409	21 1/8	658	27 1/8	932	33 1/8	1220
3 1/4	46	9 1/4	202	15 1/4	414	21 1/4	664	27 1/4	938	33 1/4	1226
3 3/8	49	9 3/8	206	15 3/8	419	21 3/8	669	27 3/8	944	33 3/8	1232
3 1/2	51	9 1/2	210	15 1/2	424	21 1/2	675	27 1/2	950	33 1/2	1238
3 5/8	54	9 5/8	214	15 5/8	429	21 5/8	680	27 5/8	956	33 5/8	1244
3 3/4	56	9 3/4	218	15 3/4	434	21 3/4	686	27 3/4	962	33 3/4	1250
3 7/8	59	9 7/8	222	15 7/8	439	21 7/8	691	27 7/8	968	33 7/8	1256
4	61	10	226	16	444	22	697	28	973	34	1262
4 1/8	64	10 1/8	230	16 1/8	449	22 1/8	703	28 1/8	979	34 1/8	1268
4 1/4	67	10 1/4	234	16 1/4	454	22 1/4	708	28 1/4	985	34 1/4	1275
4 3/8	70	10 3/8	238	16 3/8	459	22 3/8	714	28 3/8	991	34 3/8	1281
4 1/2	72	10 1/2	242	16 1/2	464	22 1/2	719	28 1/2	997	34 1/2	1287
4 5/8	75	10 5/8	246	16 5/8	469	22 5/8	725	28 5/8	1003	34 5/8	1293
4 3/4	78	10 3/4	251	16 3/4	474	22 3/4	731	28 3/4	1009	34 3/4	1299
4 7/8	81	10 7/8	255	16 7/8	479	22 7/8	736	28 7/8	1015	34 7/8	1305
5	84	11	259	17	484	23	742	29	1021	35	1311
5 1/8	87	11 1/8	263	17 1/8	489	23 1/8	747	29 1/8	1027	35 1/8	1317
5 1/4	90	11 1/4	268	17 1/4	494	23 1/4	753	29 1/4	1033	35 1/4	1323
5 3/8	93	11 3/8	272	17 3/8	499	23 3/8	759	29 3/8	1039	35 3/8	1329
5 1/2	96	11 1/2	276	17 1/2	504	23 1/2	764	29 1/2	1045	35 1/2	1335
5 5/8	99	11 5/8	281	17 5/8	509	23 5/8	770	29 5/8	1051	35 5/8	1341
5 3/4	102	11 3/4	285	17 3/4	515	23 3/4	776	29 3/4	1057	35 3/4	1348
5 7/8	106	11 7/8	289	17 7/8	520	23 7/8	781	29 7/8	1063	35 7/8	1354
6	109	12	294	18	525	24	787	30	1069	36	1360

(6') DWT-6 TYPE II 2,500 GALLON

DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS
36 1/8	1366	42 1/8	1656	48 1/8	1936	54 1/8	2195	60 1/8	2421	66 1/8	2599
36 1/4	1372	42 1/4	1662	48 1/4	1942	54 1/4	2200	60 1/4	2426	66 1/4	2602
36 3/8	1378	42 3/8	1668	48 3/8	1947	54 3/8	2205	60 3/8	2430	66 3/8	2605
36 1/2	1384	42 1/2	1674	48 1/2	1953	54 1/2	2210	60 1/2	2434	66 1/2	2608
36 5/8	1390	42 5/8	1680	48 5/8	1958	54 5/8	2215	60 5/8	2438	66 5/8	2611
36 3/4	1396	42 3/4	1686	48 3/4	1964	54 3/4	2220	60 3/4	2443	66 3/4	2614
36 7/8	1402	42 7/8	1692	48 7/8	1970	54 7/8	2225	60 7/8	2447	66 7/8	2617
37	1408	43	1698	49	1975	55	2230	61	2451	67	2619
37 1/8	1415	43 1/8	1704	49 1/8	1981	55 1/8	2235	61 1/8	2455	67 1/8	2622
37 1/4	1421	43 1/4	1710	49 1/4	1986	55 1/4	2240	61 1/4	2459	67 1/4	2625
37 3/8	1427	43 3/8	1716	49 3/8	1992	55 3/8	2245	61 3/8	2463	67 3/8	2628
37 1/2	1433	43 1/2	1722	49 1/2	1998	55 1/2	2250	61 1/2	2467	67 1/2	2630
37 5/8	1439	43 5/8	1727	49 5/8	2003	55 5/8	2255	61 5/8	2471	67 5/8	2633
37 3/4	1445	43 3/4	1733	49 3/4	2009	55 3/4	2260	61 3/4	2475	67 3/4	2635
37 7/8	1451	43 7/8	1739	49 7/8	2014	55 7/8	2265	61 7/8	2479	67 7/8	2638
38	1457	44	1745	50	2020	56	2270	62	2483	68	2640
38 1/8	1463	44 1/8	1751	50 1/8	2025	56 1/8	2275	62 1/8	2487	68 1/8	2643
38 1/4	1469	44 1/4	1757	50 1/4	2031	56 1/4	2280	62 1/4	2491	68 1/4	2645
38 3/8	1475	44 3/8	1763	50 3/8	2036	56 3/8	2284	62 3/8	2495	68 3/8	2648
38 1/2	1481	44 1/2	1769	50 1/2	2042	56 1/2	2289	62 1/2	2499	68 1/2	2650
38 5/8	1487	44 5/8	1775	50 5/8	2047	56 5/8	2294	62 5/8	2503	68 5/8	2652
38 3/4	1493	44 3/4	1780	50 3/4	2053	56 3/4	2299	62 3/4	2506	68 3/4	2655
38 7/8	1500	44 7/8	1786	50 7/8	2058	56 7/8	2304	62 7/8	2510	68 7/8	2657
39	1506	45	1792	51	2063	57	2308	63	2514	69	2659
39 1/8	1512	45 1/8	1798	51 1/8	2069	57 1/8	2313	63 1/8	2518	69 1/8	2661
39 1/4	1518	45 1/4	1804	51 1/4	2074	57 1/4	2318	63 1/4	2521	69 1/4	2663
39 3/8	1524	45 3/8	1810	51 3/8	2080	57 3/8	2323	63 3/8	2525	69 3/8	2665
39 1/2	1530	45 1/2	1815	51 1/2	2085	57 1/2	2327	63 1/2	2529	69 1/2	2667
39 5/8	1536	45 5/8	1821	51 5/8	2090	57 5/8	2332	63 5/8	2532	69 5/8	2669
39 3/4	1542	45 3/4	1827	51 3/4	2096	57 3/4	2337	63 3/4	2536	69 3/4	2671
39 7/8	1548	45 7/8	1833	51 7/8	2101	57 7/8	2341	63 7/8	2540	69 7/8	2672
40	1554	46	1839	52	2106	58	2346	64	2543	70	2674
40 1/8	1560	46 1/8	1844	52 1/8	2112	58 1/8	2350	64 1/8	2547	70 1/8	2676
40 1/4	1566	46 1/4	1850	52 1/4	2117	58 1/4	2355	64 1/4	2550	70 1/4	2677
40 3/8	1572	46 3/8	1856	52 3/8	2122	58 3/8	2360	64 3/8	2554	70 3/8	2679
40 1/2	1578	46 1/2	1862	52 1/2	2128	58 1/2	2364	64 1/2	2557	70 1/2	2680
40 5/8	1584	46 5/8	1868	52 5/8	2133	58 5/8	2369	64 5/8	2560	70 5/8	2682
40 3/4	1590	46 3/4	1873	52 3/4	2138	58 3/4	2373	64 3/4	2564	70 3/4	2683
40 7/8	1596	46 7/8	1879	52 7/8	2143	58 7/8	2378	64 7/8	2567	70 7/8	2684
41	1602	47	1885	53	2149	59	2382	65	2571	71	2685
41 1/8	1608	47 1/8	1890	53 1/8	2154	59 1/8	2387	65 1/8	2574	71 1/8	2686
41 1/4	1614	47 1/4	1896	53 1/4	2159	59 1/4	2391	65 1/4	2577	71 1/4	2687
41 3/8	1620	47 3/8	1902	53 3/8	2164	59 3/8	2395	65 3/8	2580	71 3/8	2688
41 1/2	1626	47 1/2	1908	53 1/2	2169	59 1/2	2400	65 1/2	2584	71 1/2	2688
41 5/8	1632	47 5/8	1913	53 5/8	2175	59 5/8	2404	65 5/8	2587	71 5/8	2689
41 3/4	1638	47 3/4	1919	53 3/4	2180	59 3/4	2409	65 3/4	2590		
41 7/8	1644	47 7/8	1925	53 7/8	2185	59 7/8	2413	65 7/8	2593		
42	1650	48	1930	54	2190	60	2417	66	2596		

(6') DWT-6 TYPE II 2,500 GALLON



HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

WATER FINDER #7686-1870
DAYCO/NATIONAL
DAYTON, OH
TEL: 1-800-283-2926
FAX: 1-800-688-4854

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overflow shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

Containment Solutions, Inc.
333 North Rivershire Dr., Suite 190
Conroe, TX 77304
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 5/16" deflector plate.

Pub. No. CAL 8625-DWT 8/97