

**Model DWT6 (8) 35000
DW FRP CUL Tank = 35,016 Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
0.5	22	30.5	2,631	60.5	7,095	90.5	12,517	120.5	18,351
1.0	36	31.0	2,694	61.0	7,179	91.0	12,612	121.0	18,449
1.5	53	31.5	2,758	61.5	7,263	91.5	12,708	121.5	18,547
2.0	71	32.0	2,821	62.0	7,348	92.0	12,803	122.0	18,645
2.5	90	32.5	2,886	62.5	7,433	92.5	12,899	122.5	18,742
3.0	112	33.0	2,950	63.0	7,518	93.0	12,994	123.0	18,840
3.5	135	33.5	3,015	63.5	7,604	93.5	13,090	123.5	18,938
4.0	159	34.0	3,081	64.0	7,690	94.0	13,186	124.0	19,036
4.5	184	34.5	3,147	64.5	7,776	94.5	13,282	124.5	19,134
5.0	211	35.0	3,213	65.0	7,862	95.0	13,378	125.0	19,231
5.5	239	35.5	3,280	65.5	7,948	95.5	13,474	125.5	19,329
6.0	268	36.0	3,348	66.0	8,035	96.0	13,570	126.0	19,427
6.5	298	36.5	3,415	66.5	8,122	96.5	13,667	126.5	19,524
7.0	329	37.0	3,483	67.0	8,209	97.0	13,763	127.0	19,622
7.5	361	37.5	3,552	67.5	8,296	97.5	13,859	127.5	19,719
8.0	394	38.0	3,621	68.0	8,384	98.0	13,956	128.0	19,817
8.5	428	38.5	3,690	68.5	8,472	98.5	14,053	128.5	19,914
9.0	463	39.0	3,760	69.0	8,560	99.0	14,149	129.0	20,012
9.5	499	39.5	3,830	69.5	8,648	99.5	14,246	129.5	20,109
10.0	536	40.0	3,901	70.0	8,737	100.0	14,343	130.0	20,206
10.5	574	40.5	3,972	70.5	8,825	100.5	14,440	130.5	20,304
11.0	612	41.0	4,043	71.0	8,914	101.0	14,537	131.0	20,401
11.5	651	41.5	4,115	71.5	9,003	101.5	14,634	131.5	20,498
12.0	691	42.0	4,187	72.0	9,093	102.0	14,731	132.0	20,595
12.5	732	42.5	4,260	72.5	9,182	102.5	14,828	132.5	20,692
13.0	774	43.0	4,333	73.0	9,272	103.0	14,926	133.0	20,789
13.5	816	43.5	4,406	73.5	9,362	103.5	15,023	133.5	20,885
14.0	859	44.0	4,480	74.0	9,452	104.0	15,120	134.0	20,982
14.5	903	44.5	4,554	74.5	9,542	104.5	15,218	134.5	21,079
15.0	948	45.0	4,628	75.0	9,632	105.0	15,315	135.0	21,175
15.5	993	45.5	4,703	75.5	9,723	105.5	15,413	135.5	21,272
16.0	1,039	46.0	4,778	76.0	9,814	106.0	15,510	136.0	21,368
16.5	1,086	46.5	4,853	76.5	9,905	106.5	15,608	136.5	21,464
17.0	1,133	47.0	4,929	77.0	9,996	107.0	15,706	137.0	21,561
17.5	1,181	47.5	5,005	77.5	10,088	107.5	15,803	137.5	21,657
18.0	1,229	48.0	5,082	78.0	10,179	108.0	15,901	138.0	21,753
18.5	1,279	48.5	5,159	78.5	10,271	108.5	15,999	138.5	21,849
19.0	1,329	49.0	5,236	79.0	10,363	109.0	16,097	139.0	21,945
19.5	1,379	49.5	5,313	79.5	10,455	109.5	16,195	139.5	22,040
20.0	1,430	50.0	5,391	80.0	10,547	110.0	16,293	140.0	22,136
20.5	1,482	50.5	5,469	80.5	10,639	110.5	16,390	140.5	22,231
21.0	1,534	51.0	5,548	81.0	10,732	111.0	16,488	141.0	22,327
21.5	1,587	51.5	5,626	81.5	10,824	111.5	16,586	141.5	22,422
22.0	1,640	52.0	5,705	82.0	10,917	112.0	16,684	142.0	22,517
22.5	1,694	52.5	5,785	82.5	11,010	112.5	16,782	142.5	22,612
23.0	1,749	53.0	5,864	83.0	11,103	113.0	16,880	143.0	22,707
23.5	1,804	53.5	5,944	83.5	11,197	113.5	16,978	143.5	22,802
24.0	1,860	54.0	6,025	84.0	11,290	114.0	17,076	144.0	22,897
24.5	1,916	54.5	6,105	84.5	11,384	114.5	17,174	144.5	22,992
25.0	1,973	55.0	6,186	85.0	11,477	115.0	17,272	145.0	23,086
25.5	2,030	55.5	6,267	85.5	11,571	115.5	17,370	145.5	23,181
26.0	2,088	56.0	6,349	86.0	11,665	116.0	17,468	146.0	23,275
26.5	2,146	56.5	6,431	86.5	11,759	116.5	17,566	146.5	23,369
27.0	2,205	57.0	6,513	87.0	11,854	117.0	17,665	147.0	23,463
27.5	2,265	57.5	6,595	87.5	11,948	117.5	17,763	147.5	23,557
28.0	2,325	58.0	6,678	88.0	12,043	118.0	17,861	148.0	23,650
28.5	2,385	58.5	6,761	88.5	12,137	118.5	17,959	148.5	23,744
29.0	2,446	59.0	6,844	89.0	12,232	119.0	18,057	149.0	23,837
29.5	2,507	59.5	6,927	89.5	12,327	119.5	18,155	149.5	23,931
30.0	2,569	60.0	7,011	90.0	12,422	120.0	18,253	150.0	24,024

**Model DWT6 (8) 35000
DW FRP CUL Tank = 35,016 Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
150.5	24,117	180.5	29,326	210.5	33,387
151.0	24,210	181.0	29,405	211.0	33,440
151.5	24,302	181.5	29,484	211.5	33,493
152.0	24,395	182.0	29,562	212.0	33,545
152.5	24,487	182.5	29,640	212.5	33,597
153.0	24,579	183.0	29,718	213.0	33,648
153.5	24,671	183.5	29,796	213.5	33,698
154.0	24,763	184.0	29,873	214.0	33,748
154.5	24,855	184.5	29,949	214.5	33,797
155.0	24,946	185.0	30,026	215.0	33,845
155.5	25,038	185.5	30,102	215.5	33,893
156.0	25,129	186.0	30,178	216.0	33,940
156.5	25,220	186.5	30,253	216.5	33,987
157.0	25,311	187.0	30,328	217.0	34,033
157.5	25,401	187.5	30,403	217.5	34,078
158.0	25,492	188.0	30,477	218.0	34,122
158.5	25,582	188.5	30,551	218.5	34,166
159.0	25,672	189.0	30,625	219.0	34,209
159.5	25,762	189.5	30,698	219.5	34,251
160.0	25,851	190.0	30,771	220.0	34,293
160.5	25,941	190.5	30,843	220.5	34,333
161.0	26,030	191.0	30,915	221.0	34,373
161.5	26,119	191.5	30,987	221.5	34,413
162.0	26,208	192.0	31,058	222.0	34,451
162.5	26,297	192.5	31,129	222.5	34,488
163.0	26,385	193.0	31,200	223.0	34,525
163.5	26,473	193.5	31,270	223.5	34,561
164.0	26,561	194.0	31,340	224.0	34,596
164.5	26,649	194.5	31,409	224.5	34,629
165.0	26,737	195.0	31,478	225.0	34,662
165.5	26,824	195.5	31,546	225.5	34,694
166.0	26,911	196.0	31,614	226.0	34,725
166.5	26,998	196.5	31,682	226.5	34,755
167.0	27,085	197.0	31,749	227.0	34,784
167.5	27,171	197.5	31,816	227.5	34,812
168.0	27,257	198.0	31,882	228.0	34,838
168.5	27,343	198.5	31,948	228.5	34,863
169.0	27,429	199.0	32,014	229.0	34,887
169.5	27,514	199.5	32,079	229.5	34,910
170.0	27,599	200.0	32,144	230.0	34,931
170.5	27,684	200.5	32,208	230.5	34,950
171.0	27,769	201.0	32,271	231.0	34,968
171.5	27,854	201.5	32,335	231.5	34,984
172.0	27,938	202.0	32,397	232.0	34,998
172.5	28,022	202.5	32,460	232.5	35,008
173.0	28,105	203.0	32,521	233.0	35,016
173.5	28,189	203.5	32,583		
174.0	28,272	204.0	32,643		
174.5	28,355	204.5	32,704		
175.0	28,437	205.0	32,764		
175.5	28,519	205.5	32,823		
176.0	28,601	206.0	32,882		
176.5	28,683	206.5	32,940		
177.0	28,765	207.0	32,998		
177.5	28,846	207.5	33,055		
178.0	28,927	208.0	33,112		
178.5	29,007	208.5	33,168		
179.0	29,087	209.0	33,223		
179.5	29,167	209.5	33,278		
180.0	29,247	210.0	33,333		



**CONTAINMENT
SOLUTIONS®**

HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection:

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. See vendor below or suitable equal.

Gasoil Water Finding Paste

Federal Process Corp.
800-846-7325
www.gasoila.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. **Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.**

Containment Solutions, Inc.

333 North Rivershire Dr., Suite 190
Conroe, TX 77304
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 8mm [5/16"] deflector plate.

Pub No. CAL 8-3500LDWT-CAN 5/11