

Model DWT 6 (8) 65000
DW FRP CUL Tank = 65,570 Liters

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
0.5	46	30.5	5,199	60.5	13,664	90.5	23,664	120.5	34,325
1.0	74	31.0	5,321	61.0	13,821	91.0	23,838	121.0	34,503
1.5	107	31.5	5,443	61.5	13,978	91.5	24,013	121.5	34,682
2.0	143	32.0	5,566	62.0	14,136	92.0	24,187	122.0	34,861
2.5	183	32.5	5,690	62.5	14,294	92.5	24,362	122.5	35,040
3.0	226	33.0	5,815	63.0	14,453	93.0	24,537	123.0	35,219
3.5	272	33.5	5,941	63.5	14,612	93.5	24,712	123.5	35,397
4.0	320	34.0	6,068	64.0	14,771	94.0	24,888	124.0	35,576
4.5	371	34.5	6,195	64.5	14,931	94.5	25,063	124.5	35,755
5.0	425	35.0	6,323	65.0	15,091	95.0	25,239	125.0	35,933
5.5	481	35.5	6,451	65.5	15,252	95.5	25,415	125.5	36,112
6.0	539	36.0	6,581	66.0	15,413	96.0	25,591	126.0	36,290
6.5	600	36.5	6,711	66.5	15,574	96.5	25,767	126.5	36,468
7.0	662	37.0	6,842	67.0	15,736	97.0	25,943	127.0	36,647
7.5	726	37.5	6,973	67.5	15,898	97.5	26,120	127.5	36,825
8.0	793	38.0	7,106	68.0	16,060	98.0	26,296	128.0	37,003
8.5	861	38.5	7,238	68.5	16,223	98.5	26,473	128.5	37,181
9.0	931	39.0	7,372	69.0	16,386	99.0	26,650	129.0	37,359
9.5	1,003	39.5	7,506	69.5	16,549	99.5	26,827	129.5	37,537
10.0	1,076	40.0	7,641	70.0	16,713	100.0	27,004	130.0	37,714
10.5	1,151	40.5	7,777	70.5	16,877	100.5	27,181	130.5	37,892
11.0	1,228	41.0	7,913	71.0	17,042	101.0	27,358	131.0	38,070
11.5	1,306	41.5	8,050	71.5	17,206	101.5	27,536	131.5	38,247
12.0	1,386	42.0	8,188	72.0	17,371	102.0	27,713	132.0	38,424
12.5	1,468	42.5	8,326	72.5	17,537	102.5	27,891	132.5	38,602
13.0	1,551	43.0	8,465	73.0	17,702	103.0	28,069	133.0	38,779
13.5	1,635	43.5	8,604	73.5	17,868	103.5	28,247	133.5	38,956
14.0	1,721	44.0	8,744	74.0	18,034	104.0	28,424	134.0	39,132
14.5	1,808	44.5	8,885	74.5	18,201	104.5	28,603	134.5	39,309
15.0	1,897	45.0	9,026	75.0	18,368	105.0	28,781	135.0	39,486
15.5	1,987	45.5	9,167	75.5	18,535	105.5	28,959	135.5	39,662
16.0	2,078	46.0	9,310	76.0	18,702	106.0	29,137	136.0	39,838
16.5	2,170	46.5	9,453	76.5	18,870	106.5	29,315	136.5	40,014
17.0	2,264	47.0	9,596	77.0	19,038	107.0	29,494	137.0	40,190
17.5	2,359	47.5	9,740	77.5	19,206	107.5	29,672	137.5	40,366
18.0	2,455	48.0	9,885	78.0	19,374	108.0	29,851	138.0	40,542
18.5	2,552	48.5	10,030	78.5	19,543	108.5	30,029	138.5	40,717
19.0	2,651	49.0	10,176	79.0	19,712	109.0	30,208	139.0	40,893
19.5	2,750	49.5	10,322	79.5	19,881	109.5	30,387	139.5	41,068
20.0	2,851	50.0	10,469	80.0	20,051	110.0	30,566	140.0	41,243
20.5	2,953	50.5	10,616	80.5	20,221	110.5	30,744	140.5	41,418
21.0	3,056	51.0	10,764	81.0	20,391	111.0	30,923	141.0	41,592
21.5	3,160	51.5	10,912	81.5	20,561	111.5	31,102	141.5	41,767
22.0	3,265	52.0	11,061	82.0	20,731	112.0	31,281	142.0	41,941
22.5	3,371	52.5	11,210	82.5	20,902	112.5	31,460	142.5	42,115
23.0	3,478	53.0	11,360	83.0	21,073	113.0	31,639	143.0	42,289
23.5	3,586	53.5	11,511	83.5	21,244	113.5	31,818	143.5	42,463
24.0	3,696	54.0	11,661	84.0	21,416	114.0	31,997	144.0	42,636
24.5	3,806	54.5	11,813	84.5	21,587	114.5	32,176	144.5	42,810
25.0	3,917	55.0	11,964	85.0	21,759	115.0	32,355	145.0	42,983
25.5	4,029	55.5	12,117	85.5	21,931	115.5	32,534	145.5	43,156
26.0	4,142	56.0	12,269	86.0	22,104	116.0	32,713	146.0	43,328
26.5	4,256	56.5	12,422	86.5	22,276	116.5	32,892	146.5	43,501
27.0	4,370	57.0	12,576	87.0	22,449	117.0	33,071	147.0	43,673
27.5	4,486	57.5	12,730	87.5	22,622	117.5	33,251	147.5	43,845
28.0	4,603	58.0	12,885	88.0	22,795	118.0	33,430	148.0	44,017
28.5	4,720	58.5	13,040	88.5	22,968	118.5	33,609	148.5	44,189
29.0	4,839	59.0	13,195	89.0	23,142	119.0	33,788	149.0	44,360
29.5	4,958	59.5	13,351	89.5	23,316	119.5	33,967	149.5	44,531
30.0	5,078	60.0	13,507	90.0	23,490	120.0	34,146	150.0	44,702

**Model DWT 6 (8) 65000
DW FRP CUL Tank = 65,570 Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
150.5	44,873	180.5	54,539	210.5	62,328
151.0	45,043	181.0	54,688	211.0	62,433
151.5	45,213	181.5	54,836	211.5	62,537
152.0	45,383	182.0	54,984	212.0	62,639
152.5	45,553	182.5	55,131	212.5	62,741
153.0	45,723	183.0	55,278	213.0	62,842
153.5	45,892	183.5	55,424	213.5	62,941
154.0	46,061	184.0	55,570	214.0	63,039
154.5	46,229	184.5	55,715	214.5	63,136
155.0	46,398	185.0	55,859	215.0	63,232
155.5	46,566	185.5	56,003	215.5	63,327
156.0	46,734	186.0	56,147	216.0	63,420
156.5	46,902	186.5	56,289	216.5	63,513
157.0	47,069	187.0	56,432	217.0	63,604
157.5	47,236	187.5	56,573	217.5	63,693
158.0	47,403	188.0	56,714	218.0	63,781
158.5	47,569	188.5	56,855	218.5	63,868
159.0	47,735	189.0	56,995	219.0	63,954
159.5	47,901	189.5	57,134	219.5	64,038
160.0	48,067	190.0	57,273	220.0	64,121
160.5	48,232	190.5	57,411	220.5	64,202
161.0	48,397	191.0	57,548	221.0	64,282
161.5	48,562	191.5	57,685	221.5	64,360
162.0	48,726	192.0	57,821	222.0	64,436
162.5	48,890	192.5	57,957	222.5	64,511
163.0	49,054	193.0	58,092	223.0	64,584
163.5	49,217	193.5	58,226	223.5	64,656
164.0	49,380	194.0	58,359	224.0	64,726
164.5	49,543	194.5	58,492	224.5	64,793
165.0	49,705	195.0	58,624	225.0	64,859
165.5	49,867	195.5	58,756	225.5	64,924
166.0	50,028	196.0	58,886	226.0	64,986
166.5	50,190	196.5	59,016	226.5	65,046
167.0	50,350	197.0	59,146	227.0	65,103
167.5	50,511	197.5	59,274	227.5	65,159
168.0	50,671	198.0	59,402	228.0	65,212
168.5	50,831	198.5	59,529	228.5	65,263
169.0	50,990	199.0	59,655	229.0	65,311
169.5	51,149	199.5	59,781	229.5	65,356
170.0	51,308	200.0	59,906	230.0	65,399
170.5	51,466	200.5	60,030	230.5	65,438
171.0	51,624	201.0	60,153	231.0	65,474
171.5	51,781	201.5	60,275	231.5	65,506
172.0	51,938	202.0	60,397	232.0	65,533
172.5	52,095	202.5	60,518	232.5	65,555
173.0	52,251	203.0	60,637	233.0	65,570
173.5	52,407	203.5	60,757		
174.0	52,562	204.0	60,875		
174.5	52,717	204.5	60,992		
175.0	52,871	205.0	61,109		
175.5	53,025	205.5	61,224		
176.0	53,179	206.0	61,339		
176.5	53,332	206.5	61,452		
177.0	53,484	207.0	61,565		
177.5	53,637	207.5	61,677		
178.0	53,788	208.0	61,788		
178.5	53,939	208.5	61,898		
179.0	54,090	209.0	62,007		
179.5	54,240	209.5	62,115		
180.0	54,390	210.0	62,222		



CONTAINMENT SOLUTIONS®

HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection:

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. See vendor below or suitable equal.

Gasoil Water Finding Paste

Federal Process Corp.
800-846-7325
www.gasoila.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. **Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.**

Containment Solutions, Inc.

333 North Rivershire Dr., Suite 190
Conroe, TX 77304
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 8mm [5/16"] deflector plate.

Pub No. CAL 8-6500LDWT-CAN 5/11