



STANDARD DIMENSIONS(SECONDARY TANK)				
CAPACITY GALLONS	LENGTH(L)	WIDTH (W)	HEIGHT (H)	WEIGHT
250	4' 8"	4' 8"	7' 4"	4,000 lb.
500	7' 10"	4' 8"	7' 4"	6,600 lb.
1,000	9' 5"	6' 9"	7' 4"	10,800 lb.

STANDARD EQUIPMENT:

- A-U/L 142 LISTED PRIMARY STORAGE TANK (ENTIRE TANK ASSEMBLY IS U/L 2085 LISTED FIRE-RATED)
- B-110% SECONDARY CONTAINMENT W/LOCKING ACCESS DOORS, VENT LOUVERS & PLEXIGLASS VIEW PORT
- C-U/L LISTED AIR OPERATED 1" DOUBLE DIAPHRAGM PUMP
- D-1/2" FULL COUPLING FOR AIR LINE CONNECTION (AIRLINES REMOVED FOR CLARITY)
- E-3/4" PRODUCT DISCHARGE HOSE INTO TANK
- F-AUTOMATIC AIR OPERATED HIGH LEVEL SHUTOFF VALVE W/WHISTLE
- G-U/L LISTED 3/4" X 8' HARDWALL SUCTION HOSE W/INLINE STRAINER & MALE/FEMALE QUICK CONNECT
- H-2" SUCTION TUBE W/KAMLOCK & DUSTCAP FOR PRODUCT WITHDRAWAL
- I-2" PRIMARY WORKING VENT
- J-4" OR 6" PRIMARY EMERGENCY VENT
- K-PRODUCT LEVEL GAUGE
- L-CORROSION RESISTANT COATING (STANDARD COATING: GRAY EPOXY)
- M-SUPPORT FEET FOR ANCHORING & INSPECTION
- N-3 1/8" HOLE FOR VENT PIPE
- O-4" SPARE W/PVC PLUG

- OPTIONAL EQUIPMENT:
- MALE ADAPTER WITH QUICK CONNECT
 - FEMALE ADAPTER WITH QUICK CONNECT
 - TK-15 15 GALLON TRUCKADDY
 - TK-31 31 GALLON TRUCKADDY
 - RK-25HC 25 GALLON ROLLKADDY

FIRE-RATED SAFEWASTE

AIRLINES REMOVED FOR CLARITY

PRODUCT CODE	GALLONS	DESCRIPTION	OVERALL SIZE	SHIP WT.
SAC012	SEE CHART	UL-2085 FIRE RATED SAFEWASTE TANK	SEE CHART	SEE CHART

THIS DRAWING AND DESIGN SHOWN HEREIN IS THE PROPERTY OF CONTAINMENT SOLUTIONS. USE OR COPIES THEREOF CANNOT BE MADE WITHOUT WRITTEN CONSENT.

CUSTOMER NAME: _____

APPROVED BY: _____ DATE: _____

CONTAINMENT SOLUTIONS

DRAWN BY: D. ROVANG DATE DRAWN: 01-01-14

DWG NUMBER: SAC012 SCALE: _____

REV: _____ REV BY: _____ DATE: _____ SHEET: 1 OF 1